

NEEO Remote Technical Specifications

Size & weight	<ul style="list-style-type: none">• Height: 7.1 inches (182mm)• Width: 1.9 inches (48mm)• Depth: 0.36 inch (9.2mm)• Weight: 0.17 pound (80g)	In the box	<ul style="list-style-type: none">• NEEO Remote• NEEO Docking Station• NEEO 10W Power supply incl. power cord• Documentation
System	<ul style="list-style-type: none">• ARM[®] Cortex[®] M4 single-core @ 168MHz• Running extremely efficient NEEO OS• Intelligent power management• 32MB RAM	System requirements	<ul style="list-style-type: none">• 10/100BASE-T Ethernet network for initial setup• Wi-Fi (802.11 b, g, or n) 2.4Ghz wireless network (to operate device wirelessly)• Min. iOS 8 or Android 4.4 for the NEEO App• 1 or more NEEO Brains• NEEO Account (free)
Display	<ul style="list-style-type: none">• Ultra-thin bezel display• 3 inches (diagonal) LED-backlit wide-screen multi-touch display with IPS technology• 480-by-800-pixel resolution at very high density of 291 ppi• Fingerprint-resistant coating• Fully laminated display• Unique NEEO multilayer design for thin bezels	Ports & interfaces	<ul style="list-style-type: none">• Wi-Fi (802.11b/g/n)• IEEE 802.15.4 dual antenna (6LowPAN and ready for Thread)• Accelerometer• NEEO Palm Sensor (BETA), patent pending• Capacitive sensors• Charging connector (gold plated)
Compatibility	<ul style="list-style-type: none">• TV, Sonos[®], Apple[®] TV, Roku[®], and Philips[®] Hue support• Supports cable boxes - including Cablevision[®], Verizon[®], Time Warner[®], and Comcast[®]• Supports satellite systems from Dish[®] and DirectTV[®]• over 60'000 supported devices	Power	<ul style="list-style-type: none">• 1370mAH Li-Ion battery• External 10W charger (included)• Charging via NEEO Docking Station (included)
Environmental requirements	<ul style="list-style-type: none">• Operating temperature: 32° to 95° F (0° to 35° C)• Storage temperature: -4° to 113° F (-20° to 45° C)• Avoid direct sunlight		